

Manejadoras

Alta Eficiencia



Reinicio Automático



Ventilador de varias velocidades



Bajo Nivel de Ruido



Diseño Compacto



Tubería de Cobre



Model			AHU36S1T1	AHU60S1T1
Power supply		V/Ph/Hz	208/230V/1Ph/60Hz	208/230V/1Ph/60Hz
Cooling	Capacity	Btu/h	36000	60000
	Capacity	W	10500	16000
	Input	W	3950	6420
	Rated current	A	18.1	29.48
	EER	Btu/h.W	9.11	9.35
External static pressure		pa	37.5	50
Max. input consumption (indoor		W	350	550
Max. current (indoor unit)		A	1.55	2
Indoor coil	Number of row		3	4
	Fin spacing	mm	1.5	1.5
	Fin material		Hydrophilic Aluminium Fin	Hydrophilic Aluminium Fin
	Tube outside diameter	mm	Φ7	Φ7
	Tube material		Inner Grooved	Inner Grooved
	Coil length x height x width	mm	441X40.11X378(X2)	441X53.48X420(X2)
	Number of circuit		6	8
Indoor fan motor	Model		YDK139-180	YDK139-300
	Brand		kangbao	kangbao
	Input	W	280	460
	Output	W	180	300
	Capacitor	μF	10	12.0
Indoor air flow		m ³ /h	1950	2700
Indoor noise level		dB(A)	51-56	51~57
Indoor dimension	Unit (WxHxD)	mm	500×1162×560	500×1162×560
	Packing (WxHxD)	mm	580×1210×650	580×1210×650
Indoor weight	Net	kg	56	60
	Gross	kg	61	65
	Throttle type		Orifice	Orifice
Operation temperature range			16-32	16-32
Ambient temperature range			18~43	18~43
Shipping per STD 20/40/40HQ			36/72/144	36/72/144